



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

2687-02  
Version 6.0

687.02/06 (dif. colors)  
Revision date 15 Mar 2026

Print date 8 Apr 2026

P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

2-methylpropan-1-ol  
reaction product: bisphenol-A-(epichlorhydrin)

**Supplemental hazard information**

not applicable

**2.3 Other hazards**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.  
This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**SECTION 3: Composition/information on ingredients.**

**3.2 Mixtures**

**Description**

Coating based on epoxy resin, component I

**Hazardous ingredients**

| CAS No.<br>EC No.<br>Index No.               | Substance name<br>REACH No.<br>Classification according to Regulation (EC) No 1272/2008 [CLP]   | % [mass]    |
|--|---|-------------|
| *<br>25068-38-6<br>500-033-5<br>603-074-00-8 | <b>reaction product: bisphenol-A-(epichlorhydrin)</b><br>Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319<br>Specific concentration limit (SCL)<br>Eye Irrit. 2 H319: >= 5,00 / Skin Irrit. 2 H315: >= 5,00<br>ATE (dermal): = 23,000 mg/kg<br>ATE (oral): = 15,000 mg/kg   | 12,5 < 15,0 |
| 7779-90-0<br>231-944-3<br>030-011-00-6       | <b>trizinc bis(orthophosphate)</b><br>01-2119485044-40<br>Aquatic Acute 1 H400 / Aquatic Chronic 1 H410<br>ATE (oral): > 5,000 mg/kg<br>ATE (inhalative): > 5.7 mg/L (4 h)  | 12,5 < 15,0 |
| 1330-20-7<br>215-535-7<br>601-022-00-9       | <b>o-xylene</b><br>01-2119488216-32<br>Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 /<br>Acute Tox. 4 H332 / STOT SE 3 H335 / STOT RE 2 H373 / Aquatic Chronic 3 H412<br>ATE (dermal): = 12,126 mg/kg<br>ATE (oral): = 3,523 mg/kg<br>ATE (dermal): = 1,100 mg/kg<br>ATE (inhalative): = 27,571 mg/L (4 h) | 8,00 < 10,0 |
| 1314-13-2<br>215-222-5<br>030-013-00-7       | <b>zinc oxide</b><br>01-2119463881-32<br>Aquatic Acute 1 H400 (M = 1,00 ) / Aquatic Chronic 1 H410 (M = 1,00 )<br>ATE (oral): = 7,950 mg/kg<br>ATE (oral): > 15,000 mg/kg<br>ATE (inhalative): > 5.7 mg/L (4 h)   | 5,00 < 7,00 |
| 107-98-2<br>203-539-1<br>603-064-00-3        | <b>1-methoxy-2-propanol</b><br>01-2119457435-35<br>Flam. Liq. 3 H226 / STOT SE 3 H336<br>ATE (dermal): = 13,000 mg/kg<br>ATE (dermal): > 2,000 mg/kg<br>ATE (oral): = 4,016 mg/kg<br>ATE (inhalative): = 36.7 mg/L (4 h)  | 5,00 < 7,00 |
| -<br>905-562-9<br>-                          | <b>Reaction mass of ethylbenzene and m-xylene and p-xylene</b><br>01-2119555267-33<br>Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 /<br>Acute Tox. 4 H332 / STOT SE 3 H335 / STOT RE 2 H373  | 3,00 < 5,00 |
| 78-83-1<br>201-148-0<br>603-108-00-1         | <b>2-methylpropan-1-ol</b><br>01-2119484609-23<br>Flam. Liq. 3 H226 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / STOT SE 3 H335 / STOT SE 3 H336<br>ATE (dermal): > 2,000 mg/kg<br>ATE (oral): > 2,000 mg/kg<br>ATE (inhalative): > 6.5 mg/L (4 h)  | 3,00 < 5,00 |

|                                       |  |             |
|---------------------------------------|--|-------------|
| 100-41-4<br>202-849-4<br>601-023-00-4 | <b>ethylbenzene</b><br>01-2119489370-35<br>Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Acute Tox. 4 H332 / STOT RE 2 H373 / Aquatic Chronic 3 H412<br>ATE (dermal): = 15,400 mg/kg<br>ATE (oral): = 3,500 mg/kg | 2,00 < 2,50 |
|---------------------------------------|--|-------------|

**Remark**

Full text of H- and EUH-statements: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

#### Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners. Wash contaminated clothing before reuse.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

#### Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Powder, spray mist, (water)

#### Unsuitable extinguishing media

Strong water jet

### 5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### Hazardous combustion products

Hazardous combustion products: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, smoke, Nitrogen oxides (NO<sub>x</sub>).

### 5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

Clean using cleansing agents. Do not use solvents.

### 6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities.

Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Use only spark proof tools.

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. Personal protection equipment: see section 8.

Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Additional information

Vapours are heavier than air, spread along floors and form explosive mixtures with air.

#### Advices on general occupational hygiene

When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Access only for authorised persons. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Storage class** LGK3 - Flammable liquids

#### Further information on storage conditions

Take care of instructions on label. Protect from heat and direct sunlight. Smoking is forbidden. Remove all sources of ignition. Keep container tightly closed. Store carefully closed containers upright to prevent any leaks.

### 7.3 Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

| CAS No.    | Substance name  | Source | Long-term /short-term (peak limitation)                               |
|------------|---|--------|---|
| 107-98-2   | 1-methoxy-2-propanol  | WEL    | 375 / 560 (-) mg/m <sup>3</sup><br>(may be absorbed through the skin) |
| 78-83-1    | 2-methylpropan-1-ol   | WEL    | 154 / 231 (-) mg/m <sup>3</sup>                                       |
| 14807-96-6 | Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> ) | WEL    | 1 / - (-) mg/m <sup>3</sup><br>(respirable fraction)                  |
| 100-41-4   | ethylbenzene  | WEL    | 441 / 552 (-) mg/m <sup>3</sup>                                       |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

2687-02  
Version 6.0

687.02/06 (dif. colors)  
Revision date 15 Mar 2026

Print date 8 Apr 2026

|            |   |     |   |
|------------|---|-----|---|
|            |   |     | (may be absorbed through the skin)                                      |
| 1330-20-7  | o-xylene  | WEL | 220 / 441 ( - ) mg/m <sup>3</sup><br>(may be absorbed through the skin) |
| 13463-67-7 | titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | WEL | 4 / - ( - ) mg/m <sup>3</sup><br>(respirable fraction)                  |
| 13463-67-7 | titanium dioxide [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm] | WEL | 10 / - ( - ) mg/m <sup>3</sup><br>(inhalable fraction)                  |

**Additional information**

Long-term: Long-term occupational exposure limit value

short-term: short-term occupational exposure limit value

**Biological limit values**

| CAS No.   | Substance name | Source | Value/<br>Test material  |
|-----------|----------------|--------|--|
| 1330-20-7 | o-xylene       | BMGV   | 650 mmol/mol creatinine / urine<br>end of exposure or end of shift |

**DNEL worker**

| CAS No.    | Substance name                                 | DNEL type                                | DNEL value              |
|------------|--|--|-------------------------|
| 107-98-2   | 1-methoxy-2-propanol                           | DNEL acute inhalative (local)            | 553.5 mg/m <sup>3</sup> |
| 107-98-2   | 1-methoxy-2-propanol                           | DNEL long-term dermal (systemic)         | 50.6 mg/kg              |
| 107-98-2   | 1-methoxy-2-propanol                           | DNEL long-term inhalative (systemic)     | 369 mg/m <sup>3</sup>   |
| 78-83-1    | 2-methylpropan-1-ol                            | DNEL long-term inhalative (local)        | 310 mg/m <sup>3</sup>   |
| 78-83-1    | 2-methylpropan-1-ol                            | DNEL long-term inhalative (systemic)     | 310 mg/m <sup>3</sup>   |
| 100-41-4   | ethylbenzene                                   | DNEL long-term dermal (systemic)         | 180 mg/kg               |
| 100-41-4   | ethylbenzene                                   | DNEL long-term inhalative (systemic)     | 77 mg/m <sup>3</sup>    |
| 100-41-4   | ethylbenzene                                   | DNEL acute inhalative (local)            | 293 mg/m <sup>3</sup>   |
| 1330-20-7  | o-xylene                                       | DNEL acute dermal, short-term (local)    | 289 mg/kg               |
| 1330-20-7  | o-xylene                                       | DNEL acute dermal, short-term (systemic) | 289 mg/kg               |
| 1330-20-7  | o-xylene                                       | DNEL long-term dermal (systemic)         | 180 mg/kg               |
| 1330-20-7  | o-xylene                                       | DNEL long-term inhalative (systemic)     | 77 mg/m <sup>3</sup>    |
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) | DNEL acute dermal, short-term (systemic) | 8.33 mg/kg              |
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) | DNEL long-term inhalative (systemic)     | 12.25 mg/m <sup>3</sup> |
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) | DNEL acute inhalative (systemic)         | 12.25 mg/m <sup>3</sup> |
| 7779-90-0  | trizinc bis(orthophosphate)                    | DNEL long-term dermal (systemic)         | 83 mg/kg                |
| 7779-90-0  | trizinc bis(orthophosphate)                    | DNEL long-term inhalative (systemic)     | 5 mg/m <sup>3</sup>     |
| 1314-13-2  | zinc oxide                                     | DNEL long-term dermal (systemic)         | 83 mg/kg                |
| 1314-13-2  | zinc oxide                                     | DNEL long-term inhalative (systemic)     | 5 mg/m <sup>3</sup>     |

**PNEC**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**

2687-02  
Version 6.0

687.02/06 (dif. colors)  
Revision date 15 Mar 2026

Print date 8 Apr 2026

| CAS No.      | Substance name                                 | PNEC type                          | PNEC Value   |
|--------------|--|------------------------------------|--------------|
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC aquatic, intermittent release | 100 mg/L     |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC sewage treatment plant (STP)  | 100 mg/L     |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC sediment, marine water        | 4.17 mg/kg   |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC soil, freshwater              | 2.47 mg/kg   |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC sediment, freshwater          | 41.6 mg/kg   |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC aquatic, freshwater           | 10 mg/L      |
| 107-98-2     | 1-methoxy-2-propanol                           | PNEC aquatic, marine water         | 1 mg/L       |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC aquatic, intermittent release | 11 mg/L      |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC sewage treatment plant (STP)  | 10 mg/L      |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC sediment, marine water        | 0.152 mg/kg  |
| * 78-83-1    | 2-methylpropan-1-ol                            | PNEC soil, freshwater              | 0.0699 mg/kg |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC sediment, freshwater          | 1.52 mg/kg   |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC aquatic, freshwater           | 0.4 mg/L     |
| 78-83-1      | 2-methylpropan-1-ol                            | PNEC aquatic, marine water         | 0.04 mg/L    |
| 100-41-4     | ethylbenzene                                   | PNEC aquatic, intermittent release | 0.1 mg/L     |
| 100-41-4     | ethylbenzene                                   | PNEC sewage treatment plant (STP)  | 9.6 mg/L     |
| 100-41-4     | ethylbenzene                                   | PNEC sediment, marine water        | 1.37 mg/kg   |
| 100-41-4     | ethylbenzene                                   | PNEC sediment, freshwater          | 13.7 mg/kg   |
| 100-41-4     | ethylbenzene                                   | PNEC aquatic, freshwater           | 0.1 mg/L     |
| 100-41-4     | ethylbenzene                                   | PNEC aquatic, marine water         | 0.01 mg/L    |
| 100-41-4     | ethylbenzene                                   | PNEC soil, freshwater              | 2.68 mg/kg   |
| 1330-20-7    | o-xylene                                       | PNEC aquatic, intermittent release | 0.327 mg/L   |
| 1330-20-7    | o-xylene                                       | PNEC sewage treatment plant (STP)  | 6.58 mg/L    |
| 1330-20-7    | o-xylene                                       | PNEC sediment, marine water        | 12.46 mg/kg  |
| 1330-20-7    | o-xylene                                       | PNEC sediment, freshwater          | 12.46 mg/kg  |
| 1330-20-7    | o-xylene                                       | PNEC aquatic, freshwater           | 0.327 mg/L   |
| 1330-20-7    | o-xylene                                       | PNEC aquatic, marine water         | 0.327 mg/L   |
| 1330-20-7    | o-xylene                                       | PNEC soil, freshwater              | 2.31 mg/kg   |
| 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) | PNEC aquatic, intermittent release | 0.018 mg/L   |
| 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) | PNEC sewage treatment plant (STP)  | 10 mg/L      |
| * 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) | PNEC sediment, marine water        | 0.0996 mg/kg |
| 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) | PNEC sediment, freshwater          | 0.996 mg/kg  |
| 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) | PNEC soil, freshwater              | 0.196 mg/kg  |
| 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) | PNEC aquatic, freshwater           | 0.006 mg/L   |
| * 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) | PNEC aquatic, marine water         | 0.0006 mg/L  |
| 7779-90-0    | trizinc bis(orthophosphate)                    | PNEC sewage treatment plant (STP)  | 100 mg/L     |
| 7779-90-0    | trizinc bis(orthophosphate)                    | PNEC sediment, marine water        | 56.5 mg/kg   |
| 7779-90-0    | trizinc bis(orthophosphate)                    | PNEC sediment, freshwater          | 117.8 mg/kg  |
| 7779-90-0    | trizinc bis(orthophosphate)                    | PNEC aquatic, freshwater           | 20.6 mg/L    |
| 7779-90-0    | trizinc bis(orthophosphate)                    | PNEC aquatic, marine water         | 6.1 mg/L     |

|           |                             |                       |            |
|-----------|-----------------------------|-----------------------|------------|
| 7779-90-0 | trizinc bis(orthophosphate) | PNEC soil, freshwater | 35.6 mg/kg |
|-----------|-----------------------------|-----------------------|------------|

## 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### Personal protection equipment

#### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used:

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material  $\geq$  0.4 mm

Breakthrough time  $\geq$  480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

#### Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Eye glasses with side protection: EN 166

#### Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Anti-static clothing including shoes are recommended.

#### Remark

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|   |  |
|---|--|
| Physical state                          | Liquid                                     |
| Colour                                  | yellow                                     |
| Odour                                   | characteristic                             |
| pH at 20 °C                             | not determined                             |
| Melting point/freezing point            | 120 °C                                     |
| Initial boiling point and boiling range | 108 °C                                     |
| Flash point                             | 23 °C                                      |
| flammability                            | Flammable liquid and vapour.               |
| Lower explosion limit at 20°C           | 1 Vol-%<br>Source: ethylbenzene            |
| Upper explosion limit at 20°C           | 13.1 Vol-%<br>Source: 1-methoxy-2-propanol |
| Vapour pressure at 20°C                 | 2.0 mbar                                   |
| Relative vapour density                 | not applicable                             |
| Density at 20 °C                        | 1.0 kg/l                                   |
| Water solubility at 20°C                | practically insoluble                      |

|  |                              |
|--|------------------------------|
| Partition coefficient: n-octanol/water | see section 12               |
| Auto-ignition temperature              | 270 °C                       |
|  | Source: 1-methoxy-2-propanol |
| Decomposition temperature              | not determined               |
| Kinematic viscosity at 20 °C           | 400 mm <sup>2</sup> /s       |
| Dynamic viscosity at 20 °C             | 400 mPas                     |
| Viscosity                              | > 60s / 4mm                  |
| particle characteristics               | not applicable               |

## 9.2 Other information

|                 |        |
|-----------------|--------|
| Solid content   | 75.3 % |
| solvent content | 24.7 % |
| Water content   | 0 %    |

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### 1-methoxy-2-propanol

LD50: dermal (Rabbit): = 13,000 mg/kg

LD50: dermal (Rat): > 2,000 mg/kg

LD50: oral (Rat): = 4,016 mg/kg

LC50: inhalative (Rat): = 36.7 mg/L (4 h)

#### 2-methylpropan-1-ol

LD50: dermal (Rat): > 2,000 mg/kg

LD50: oral (Rat): > 2,000 mg/kg; (OECD 401)

LC50: inhalative (Rat): > 6.5 mg/L (4 h)

#### ethylbenzene

LD50: dermal (Rabbit): = 15,400 mg/kg

LD50: oral (Rat): = 3,500 mg/kg

#### o-xylene

LD50: dermal (Rabbit): = 12,126 mg/kg

LD50: oral (Rat): = 3,523 mg/kg; (OECD 423)

LD50: dermal (Rat): = 1,100 mg/kg

LC50: inhalative (Rat): = 27,571 mg/L (4 h)

**reaction product: bisphenol-A-(epichlorhydrin)**

LD50: dermal (Rabbit): = 23,000 mg/kg

LD50: oral (Rat): = 15,000 mg/kg

**trizinc bis(orthophosphate)**

LD50: oral (Rat): > 5,000 mg/kg

LC50: inhalative (Rat): > 5.7 mg/L (4 h)

**zinc oxide**

LD50: oral (Mouse): = 7,950 mg/kg

LD50: oral (Rat): > 15,000 mg/kg

LC50: inhalative (Rat): > 5.7 mg/L (4 h)

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Overall assessment on CMR properties**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## 11.2 Information on other hazards

**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

**o-xylene**

EC50 < 1,000 mg/L (15 h)

**Algae toxicity**

**2-methylpropan-1-ol**

ErC50: (Scenedesmus subspicatus): = 1,250 mg/L (48 h)

**ethylbenzene**

ErC50: (Pseudokirchneriella subcapitata): = 4.6 mg/L (72 h)

ErC50: (Pseudokirchneriella subcapitata): = 5.4 mg/L (72 h)

**o-xylene**

ErC50: (Scenedesmus subspicatus): < 100 mg/L (72 h)

Method: OECD 201

**reaction product: bisphenol-A-(epichlorhydrin)**

ErC50: = 11 mg/L (72 h)

**trizinc bis(orthophosphate)**

ErC50: > 100 mg/L

**zinc oxide**

ErC50: (Scenedesmus subspicatus): = 58.8 mg/L (72 h)

**Daphnia toxicity**

**1-methoxy-2-propanol**

EC50 (Daphnia magna (Big water flea)): = 23,300 mg/L (48 h)

**2-methylpropan-1-ol**

EC50 (Daphnia magna (Big water flea)): = 1,439 mg/L (48 h)

**ethylbenzene**

EC50 (Daphnia magna (Big water flea)): = 2.1 mg/L (48 h)

**o-xylene**

EC50 (Daphnia magna (Big water flea)): > 100 mg/L (48 h)

Method: OECD 202

EC50 (Daphnia magna (Big water flea)): < 165 mg/L (48 h)

**reaction product: bisphenol-A-(epichlorhydrin)**

EC50 = 1.8 mg/L (48 h)

**trizinc bis(orthophosphate)**

EC50 (Daphnia magna (Big water flea)): > 1,000 mg/L (48 h)

**zinc oxide**

EC50 (Daphnia magna (Big water flea)): > 100 mg/L (48 h)

**Fish toxicity**

**2-methylpropan-1-ol**

LC50: (Leuciscus idus (golden orfe)): > 500 mg/L (96 h)

Method: OECD 203

**ethylbenzene**

LC50: (Pimephales promelas (fathead minnow)): = 12.1 mg/L (96 h)

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 4.2 mg/L (96 h)

Method: OECD 203

**o-xylene**

LC50: (Oncorhynchus mykiss (Rainbow trout)): < 100 mg/L (96 h)

Method: OECD 203

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 14 mg/L (96 h)

**reaction product: bisphenol-A-(epichlorhydrin)**

LC50: (Leuciscus idus (golden orfe)): = 2 mg/L (96 h)

**trizinc bis(orthophosphate)**

LC50: (Oncorhynchus mykiss (Rainbow trout)): > 1,000 mg/L (96 h)

LC50: > 5,000 mg/L (96 h)

**zinc oxide**

LC50: (Danio rerio (zebrafish)): > 10,000 mg/L (96 h)

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

No information available.

**12.4 Mobility in soil**

No information available.

**12.5 Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6 Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7 Other adverse effects**

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### Waste codes/waste designations according to EWC/AVV

080111\* - Waste paint and varnish containing organic solvents or other dangerous substances  
\* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

### 14.1 UN number or ID number

UN 1263

### 14.2 UN proper shipping name

#### Land transport (ADR/RID)

Paint

#### Sea transport (IMDG)

Paint

#### Air transport (ICAO-TI / IATA-DGR)

Paint

### 14.3 Transport hazard class(es)

|                                    |   |
|------------------------------------|---|
| Land transport (ADR/RID)           | 3 |
| Sea transport (IMDG)               | 3 |
| Air transport (ICAO-TI / IATA-DGR) | 3 |

### 14.4 Packing group

|                                    |     |
|------------------------------------|-----|
| Land transport (ADR/RID)           | III |
| Sea transport (IMDG)               | III |
| Air transport (ICAO-TI / IATA-DGR) | III |

### 14.5 Environmental hazards

|                          |                           |
|--------------------------|---------------------------|
| Land transport (ADR/RID) | ENVIRONMENTALLY HAZARDOUS |
| Sea transport (IMDG)     | Marine pollutant          |

### 14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

### 14.8 Additional information

#### Land transport (ADR/RID)

Tunnel restriction code: D/E  
Limited quantity (LQ): 5 ltr  
Hazard identification number (Kemler No.): 30

#### Sea transport (IMDG)

EmS-No.: F-E, S-E  
Limited quantity (LQ): 5 ltr

#### Air transport (ICAO-TI / IATA-DGR)

Limited quantity (LQ): 10 Liter

## SECTION 15: Regulatory information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### EU legislation

#### Authorisations and/or restrictions on use

##### Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 03, 40

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 247 g/l

#### Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(j): 500 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 289 g/L

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

#### \* Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

#### Hazard categories / Named dangerous substances

E2 Hazardous to the aquatic environment in Category Chronic 2

Quantity 1: 200t; Quantity 2: 500t

P5c FLAMMABLE LIQUIDS

Quantity 1: 5,000t; Quantity 2: 50,000t

#### National regulations

Observe in addition any national regulations!

#### Water hazard class

#### Substance/product listed in the following inventories

Toxic Substances Control Act - US

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.  |
| H226 | Flammable liquid and vapour.   |
| H304 | May be fatal if swallowed and enters airways.  |
| H312 | Harmful in contact with skin.  |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.   |
| H318 | Causes serious eye damage.   |
| H319 | Causes serious eye irritation.   |
| H332 | Harmful if inhaled.  |
| H335 | May cause respiratory irritation.  |
| H336 | May cause drowsiness or dizziness.   |
| H373 | May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). |
| H400 | Very toxic to aquatic life.  |
| H410 | Very toxic to aquatic life with long lasting effects.  |
| H412 | Harmful to aquatic life with long lasting effects.   |

### Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

|                   |                        |
|-------------------|------------------------|
| Flam. Liq. 3      | On basis of test data. |
| Skin Irrit. 2     | Calculation method.    |
| Skin Sens. 1      | Calculation method.    |
| Eye Dam. 1        | Calculation method.    |
| Aquatic Chronic 2 | Calculation method.    |

### Key literature references and sources for data

Data arise from reference works and literature.

#### **Abbreviations and acronyms**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
OEL: Occupational Exposure Limit Value  
BLV: Biological limit values  
CAS: Chemical Abstracts Service  
CLP: Classification, Labelling and Packaging  
CMR: Carcinogenic, Mutagenic and Reprotoxic  
DIN: German Institute for Standardization / German industrial standard  
DNEL: Derived No-Effect Level  
EAKV: European Waste Catalogue Directive  
EC: Effective Concentration  
EC: European Community  
EN: European Standard  
EU/EEA: European Economic Area  
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations  
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk  
ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air  
IMDG Code: International Maritime Code for Dangerous Goods  
ISO: International Organization for Standardization  
LC: Lethal Concentration  
LD: Lethal Dose  
:  
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships  
OECD: Organisation for Economic Cooperation and Development  
PBT: persistent, bioaccumulative, toxic  
PNEC: Predicted No Effect Concentration  
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals  
UN: United Nations  
VOC: Volatile Organic Compounds  
vPvB: very persistent and very bioaccumulative

#### **Indication of changes**

\* Data changed compared with the previous version.  
replaces version: 5.0  
replaces revision of: 8 Dec 2025