

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation

416-186-003K HVS 186 K (dif. colors)
CHING-HYDROVERSAL-PRIMER
60-80 µm
UFI: 885H-V2CR-6007-A9XJ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Corrosion Protection and Industrial Coatings.

1.3 Details of the supplier of the safety data sheet

Supplier

CHEMISCHE INDUSTRIE ERLANGEN GMBH
Rathenastr. 18 Telephone: +49 9131 3006-0
91052 Erlangen E-mail: info@ching-coatings.com
Germany Website: https://www.ching-coatings.com

Department responsible for information

E-mail (competent person) msds@ching-coatings.com

1.4 Emergency telephone number

Emergency telephone number: +49 9131 3006 91
Only available during office hours.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

- * Muta. 1B H340 May cause genetic defects.
- * Carc. 1B H350 May cause cancer.
- Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS08

Signal word

- * Danger

Hazard statements

H340 May cause genetic defects.
H350 May cause cancer.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.
P280 Wear protective gloves and eye protection/face protection.
P308 + P313 IF exposed or concerned: Get medical advice/attention.

Hazard components for labelling

- * Naphtha (petroleum), hydrotreated heavy

Supplemental hazard information

EUH208 Contains Cobalt, borate neodecanoate. May produce an allergic reaction.

Other labelling

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

416-186-003K
 Version 4.0

HVS 186 K (dif. colors)
 Revision date 18 Dec 2025

Print date 19 Feb 2026

Restricted to professional users.

2.3 Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
 This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

Coating based on waterborne synthetic resins

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	% [mass]
5131-66-8 225-878-4 603-052-00-8	3-butoxypropan-2-ol 01-2119475527-28 Skin Irrit. 2 H315 / Eye Irrit. 2 H319 ATE (dermal): > 2,000 mg/kg ATE (oral): = 3,300 mg/kg	5,00 < 7,00
7779-90-0 231-944-3 030-011-00-6	trizinc bis(orthophosphate) 01-2119485044-40 Aquatic Acute 1 H400 / Aquatic Chronic 1 H410 ATE (oral): > 5,000 mg/kg ATE (inhalative): > 5.7 mg/L (4 h)	2,00 < 2,50
34590-94-8 252-104-2 -	Dipropylene glycol methylether 01-2119450011-60 ATE (dermal): = 9,510 mg/kg ATE (oral): > 5,135 mg/kg Substance with a common (EC) occupational exposure limit value.	2,00 < 2,50
78-92-2 201-158-5 603-127-00-5	(±)-butan-2-ol 01-2119475146-36 Flam. Liq. 3 H226 / Eye Irrit. 2 H319 / STOT SE 3 H335 / STOT SE 3 H336	1,00 < 2,00
1336-21-6 215-647-6 007-001-01-2	ammonia 01-2119488876-14 Skin Corr. 1B H314 / Aquatic Acute 1 H400 Specific concentration limit (SCL) STOT SE 3 H335: >= 5,00 ATE (oral): > 350 mg/kg	0,300 < 0,500
* 64742-48-9 265-150-3 649-327-00-6	Naphtha (petroleum), hydrotreated heavy 01-2119457273-39 Asp. Tox. 1 H304 / Muta. 1B H340 / Carc. 1B H350 ATE (oral): > 2,000 mg/kg	0,100 < 0,150
22464-99-9 245-018-1 607-230-00-6	2-ethylhexanoic acid 01-2119979088-21 Repr. 2 H361 ATE (oral): > 2,000 mg/kg ATE (dermal): > 2,000 mg/kg	0,100 < 0,150
68457-13-6 270-601-2 -	Cobalt, borate neodecanoate 01-2119526957-25 Acute Tox. 4 H302 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Repr. 2 H361 / STOT RE 1 H372 / Aquatic Acute 1 H400 / Aquatic Chronic 2 H411 ATE (dermal): > 2,000 mg/kg ATE (oral): = 1,098 mg/kg	0,100 < 0,150

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners. Wash contaminated clothing before reuse.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

Hazardous combustion products

Hazardous combustion products: Carbon dioxide (CO₂), Carbon monoxide, smoke, Nitrogen oxides (NO_x).

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



416-186-003K
 Version 4.0

HVS 186 K (dif. colors)
 Revision date 18 Dec 2025

Print date 19 Feb 2026

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrsiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Storage class

LGK6.1D - Non-combustible substances of acute toxicity, category 3 / hazardous substances that are toxic or produce chronic effects

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
78-92-2	(±)-butan-2-ol	WEL	308 / 462 (-) mg/m ³
34590-94-8	Dipropylene glycol methylether	WEL	308 / - (-) mg/m ³ (may be absorbed through the skin)
1317-65-3	Limestone	WEL	10 / - (-) mg/m ³ (inhalable fraction)
1317-65-3	Limestone	WEL	4 / - (-) mg/m ³ (respirable fraction)
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	WEL	800 / - (-) mg/m ³ (> or = C7, Cycloalkanes)
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	WEL	1,200 / - (-) mg/m ³ (alkanes >= C7)
14807-96-6	Talc (Mg3H2(SiO3)4)	WEL	1 / - (-) mg/m ³ (respirable fraction)

Additional information

Long-term: Long-term occupational exposure limit value
 short-term: short-term occupational exposure limit value

Biological limit values

* No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
22464-99-9	2-ethylhexanoic acid	DNEL long-term dermal (systemic)	6.49 mg/kg
22464-99-9	2-ethylhexanoic acid	DNEL long-term inhalative (systemic)	32.97 mg/m ³
5131-66-8	3-butoxypropan-2-ol	DNEL long-term dermal	52 mg/kg

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

		(systemic)	
5131-66-8	3-butoxypropan-2-ol	DNEL long-term inhalative (systemic)	147 mg/m ³
68457-13-6	Cobalt, borate neodecanoate	DNEL long-term inhalative (local)	169.5 mg/m ³
34590-94-8	Dipropylene glycol methylether	DNEL long-term dermal (systemic)	283 mg/kg
34590-94-8	Dipropylene glycol methylether	DNEL long-term inhalative (systemic)	308 mg/m ³
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	DNEL long-term inhalative (local)	180 mg/m ³
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	DNEL long-term inhalative (systemic)	1,200 mg/m ³
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	DNEL acute inhalative (systemic)	1,300 mg/m ³
* 64742-48-9	Naphtha (petroleum), hydrotreated heavy	DNEL acute inhalative (local)	640 mg/m ³
1336-21-6	ammonia	DNEL long-term dermal (systemic)	6.8 mg/kg
1336-21-6	ammonia	DNEL long-term inhalative (systemic)	47.6 mg/m ³
7779-90-0	trizinc bis(orthophosphate)	DNEL long-term dermal (systemic)	83 mg/kg
7779-90-0	trizinc bis(orthophosphate)	DNEL long-term inhalative (systemic)	5 mg/m ³

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
22464-99-9	2-ethylhexanoic acid	PNEC sediment, marine water	0.637 mg/kg
22464-99-9	2-ethylhexanoic acid	PNEC sewage treatment plant (STP)	71.7 mg/L
22464-99-9	2-ethylhexanoic acid	PNEC soil, freshwater	1.06 mg/kg
22464-99-9	2-ethylhexanoic acid	PNEC sediment, freshwater	6.37 mg/kg
22464-99-9	2-ethylhexanoic acid	PNEC aquatic, freshwater	0.36 mg/L
22464-99-9	2-ethylhexanoic acid	PNEC aquatic, marine water	0.036 mg/L
5131-66-8	3-butoxypropan-2-ol	PNEC aquatic, intermittent release	5.25 mg/L
5131-66-8	3-butoxypropan-2-ol	PNEC sewage treatment plant (STP)	10 mg/L
5131-66-8	3-butoxypropan-2-ol	PNEC sediment, marine water	0.236 mg/kg
5131-66-8	3-butoxypropan-2-ol	PNEC sediment, freshwater	2.36 mg/kg
5131-66-8	3-butoxypropan-2-ol	PNEC aquatic, freshwater	0.525 mg/L
5131-66-8	3-butoxypropan-2-ol	PNEC aquatic, marine water	0.052 mg/L
5131-66-8	3-butoxypropan-2-ol	PNEC soil, freshwater	0.16 mg/kg
68457-13-6	Cobalt, borate neodecanoate	PNEC sediment, marine water	9.5 mg/kg
68457-13-6	Cobalt, borate neodecanoate	PNEC sewage treatment plant (STP)	0.37 mg/L
68457-13-6	Cobalt, borate neodecanoate	PNEC sediment, freshwater	9.5 mg/kg
68457-13-6	Cobalt, borate neodecanoate	PNEC aquatic, freshwater	0.51 mg/L
68457-13-6	Cobalt, borate neodecanoate	PNEC aquatic, marine water	2.36 mg/L
68457-13-6	Cobalt, borate neodecanoate	PNEC soil, freshwater	10.9 mg/kg
34590-94-8	Dipropylene glycol methylether	PNEC aquatic, intermittent release	190 mg/L
34590-94-8	Dipropylene glycol methylether	PNEC sewage treatment plant (STP)	4,168 mg/L
34590-94-8	Dipropylene glycol methylether	PNEC sediment, marine water	7.02 mg/kg

34590-94-8	Dipropylene glycol methylether	PNEC sediment, freshwater	70.2 mg/kg
34590-94-8	Dipropylene glycol methylether	PNEC aquatic, freshwater	19 mg/L
34590-94-8	Dipropylene glycol methylether	PNEC aquatic, marine water	1.9 mg/L
34590-94-8	Dipropylene glycol methylether	PNEC soil, freshwater	2.74 mg/kg
1336-21-6	ammonia	PNEC aquatic, freshwater	0.001 mg/L
1336-21-6	ammonia	PNEC aquatic, marine water	0.001 mg/L
7779-90-0	trizinc bis(orthophosphate)	PNEC sewage treatment plant (STP)	100 mg/L
7779-90-0	trizinc bis(orthophosphate)	PNEC sediment, marine water	56.5 mg/kg
7779-90-0	trizinc bis(orthophosphate)	PNEC sediment, freshwater	117.8 mg/kg
7779-90-0	trizinc bis(orthophosphate)	PNEC aquatic, freshwater	20.6 mg/L
7779-90-0	trizinc bis(orthophosphate)	PNEC aquatic, marine water	6.1 mg/L
7779-90-0	trizinc bis(orthophosphate)	PNEC soil, freshwater	35.6 mg/kg

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used:

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material \geq 0.4 mm

Breakthrough time \geq 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Anti-static clothing including shoes are recommended.

Remark

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid	
Colour	brown	
Odour	characteristic	
pH at 23.0 °C (25%)	7.5 - 9.5	DIN 53785
Melting point/freezing point	-85 °C	
	Source: 3-butoxypropan-2-ol	
Initial boiling point and boiling range	100 °C	
Flash point	not applicable	

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

flammability	not applicable
Lower explosion limit at 20°C	1.1 Vol-% Source: Dipropylene glycol methylether
Upper explosion limit at 20°C	14 Vol-% Source: Dipropylene glycol methylether
Vapour pressure at 20°C	19.484 mbar
Relative vapour density	not applicable
Density at 20 °C	1.4 kg/l
Water solubility at 20°C	partially soluble
Partition coefficient: n-octanol/water	see section 12
Auto-ignition temperature	260 °C Source: 3-butoxypropan-2-ol
Decomposition temperature	not determined
Kinematic viscosity at 20 °C	90-95 KU
Dynamic viscosity at 20 °C	90-95 KU
Viscosity	60s / 4mm
particle characteristics	not applicable

9.2 Other information

Solid content	59.2 %
solvent content	10.2 %
Water content	30 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

2-ethylhexanoic acid

LD50: oral (Rat): > 2,000 mg/kg

LD50: dermal (Rabbit): > 2,000 mg/kg

3-butoxypropan-2-ol

LD50: dermal (Rat): > 2,000 mg/kg; (OECD 402)

LD50: oral (Rat): = 3,300 mg/kg; (OECD 423)

Cobalt, borate neodecanoate

LD50: dermal (Rabbit): > 2,000 mg/kg

LD50: oral (Rat): = 1,098 mg/kg

Dipropylene glycol methylether

LD50: dermal (Rabbit): = 9,510 mg/kg

LD50: oral (Rat): > 5,135 mg/kg; (OECD 401)

* **Naphtha (petroleum), hydrotreated heavy**

LD50: oral (Rat): > 2,000 mg/kg

ammonia

LD50: oral (Rat): > 350 mg/kg

trizinc bis(orthophosphate)

LD50: oral (Rat): > 5,000 mg/kg

LC50: inhalative (Rat): > 5.7 mg/L (4 h)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

* May cause genetic defects.

* May cause cancer.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Algae toxicity

3-butoxypropan-2-ol

ErC50: (Pseudokirchneriella subcapitata): > 1,000 mg/L (96 h)

Cobalt, borate neodecanoate

ErC50: (Pseudokirchneriella subcapitata): = 0.41 mg/L (72 h)

Dipropylene glycol methylether

ErC50: (Selenastrum capricornutum): = 969 mg/L (96 h)

trizinc bis(orthophosphate)

ErC50: > 100 mg/L

Daphnia toxicity

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878

416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

3-butoxypropan-2-ol

EC50 (Daphnia magna (Big water flea)): > 1,000 mg/L (48 h)
Method: OECD 202

Cobalt, borate neodecanoate

EC50 (Daphnia magna (Big water flea)): = 9.2 mg/L (48 h)

Dipropylene glycol methylether

EC50 (Daphnia magna (Big water flea)): = 1,919 mg/L (48 h)

ammonia

EC50 (Daphnia magna (Big water flea)): = 25.4 mg/L (48 h)

trizinc bis(orthophosphate)

EC50 (Daphnia magna (Big water flea)): > 1,000 mg/L (48 h)

Fish toxicity

3-butoxypropan-2-ol

LC50: (Pimephales promelas (fathead minnow)): > 100 mg/L (96 h)

Cobalt, borate neodecanoate

LC50: = 275 mg/L (96 h)

Dipropylene glycol methylether

LC50: (Pimephales promelas (fathead minnow)): > 10,000 mg/L (96 h)

trizinc bis(orthophosphate)

LC50: (Oncorhynchus mykiss (Rainbow trout)): > 1,000 mg/L (96 h)

LC50: > 5,000 mg/L (96 h)

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080111* - Waste paint and varnish containing organic solvents or other dangerous substances
* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Land transport (ADR/RID) not applicable

Sea transport (IMDG) not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

not applicable

Sea transport (IMDG)

not applicable

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 03, 40

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 144 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(i): 140 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 144 g/L

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]

Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

* **National regulations**

Observe in addition any national regulations!

Water hazard class

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226 Flammable liquid and vapour.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) 2020/878



416-186-003K
Version 4.0

HVS 186 K (dif. colors)
Revision date 18 Dec 2025

Print date 19 Feb 2026

H302	Harmful if swallowed.
* H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
* H340	May cause genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
* H350	May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H361	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H372	Causes damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

* Muta. 1B	Calculation method.
* Carc. 1B	Calculation method.
Aquatic Chronic 3	Calculation method.

Key literature references and sources for data

Data arise from reference works and literature.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

EU/EEA: European Economic Area

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

replaces version: 3.2

replaces revision of: 18 Oct 2025